

The ultimate solvent for industrial and precision cleaning.

SolSafe 245 is engineered to quickly and effectively remove heavy grease and oil from metal and painted surfaces. Its powerful formula is ideal for surface preparation prior to coating or for heavier degreasing tasks.

SolSafe 245 is a residue-free solution designed for cleaning surfaces in applications where water cannot be used. Its high-solvency formula rapidly cuts through heavy oils and grease to help reduce cleaning time while improving operational efficiency and safety.

SolSafe 245 performs exceptionally well in hand-wipe applications, immersion tanks, and ultrasonic parts washing systems. Its slow evaporation rate, easy filtration, and extended bath life — up to six times longer than many common solvents — help reduce solvent consumption and lower operating costs.

SolSafe 245 helps improve workplace safety and features a high flash point and a non-caustic, non-corrosive formula. It provides a safer alternative to many traditional solvents without sacrificing cleaning performance.

SolSafe 245 is available in bulk liquid for immersion, parts washing, and manual cleaning applications, and in aerosol form for convenient spot cleaning and field use. Both options deliver the same high-performance cleaning and degreasing results.



- **Non-Caustic / Non-Corrosive**
- **High Flash Point Formula**
- **High Dielectric Strength**
- **High Solvency Strength**
- **Non-Aqueous**
- **Safe on All Metals**
- **Safe on Painted Surfaces**
- **Dries Residue Free**
- **Fresh Scent**

REMOVES	APPLICATIONS	AVAILABLE PRODUCTS
Lubricants, Grease, Adhesives, Cutting Oils, Hydraulic Fluid, Waxes / Paraffin, Oil-Based Foulants	Surface cleaning of: All Metal Parts / Surfaces, Electrical Switchgear and Equipment, Valves / Pumps, Heavy Equipment	BF1024 - 1 Gal Can (4/cs)
		BF1025 - 5 Gal Pail
		BF1026 - 55 Gal Drum
		BF1029 - 275 Gal Tote
		BF1022 - Aero - 15 oz (12/cs)

DIRECTIONS

1. Remove all loose dirt and soil prior to cleaning.
2. Apply SolSafe[®] 245 directly to the surface to be cleaned.
3. Let penetrate for 30 seconds to two minutes.
4. Wipe dry as needed. Drying process may be accelerated by heating parts with warm, dry air. Water rinse is not required.

NOTE: SolSafe is highly effective for parts washing applications and manual cleaning.

Item #	BF1024, BF1025, BF1026, BF1027, BF1029
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal, 275 gal
Container Types & Weights:	Steel Can - 1 gal - 8.25 lbs
	Steel Pail - 5 gal - 41.5 lbs
	Steel Drum - 55 gal - 442.5 lbs
	Tote - 275 gal - 2075 lbs

Scent:	Light Clean Scent, Solvent
Color:	Clear / Colorless
Flash Point:	145°F (62.7°C)
Base Type:	Petroleum
Solvency/KB:	106
Dielectric Strength:	53,600 v/cm
VOC Content:	840 g/L
pH:	Not Measured
Relative Density:	0.84
Restricted from Sale:	None
California Prop 65 Warning:	None

DANGER: Combustible liquid. May be fatal if swallowed and enters airways.

PREVENTION: Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Wear eye protection, face protection, protective clothing, protective gloves.

RESPONSE: IF SWALLOWED: Immediately call a poison center or doctor / physician. Do NOT induce vomiting. In case of fire: Use carbon dioxide (CO₂), Foam, dry chemical, dry extinguishing powder to extinguish.

STORAGE: Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to hazardous or special waste collection point, in accordance with local, regional, national and / or international regulation.

EMERGENCY TELEPHONE NUMBER PERS:
(800) 633-8253

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY**



07292026