

The ultimate solution for quickly dissolving ready-mix and concentrated coal tar sealers.

Tarpedo was engineered for dissolving and removing the toughest coal tar sealers and reduces cleaning time so you can focus on more important things. In as little as 30 seconds, Tarpedo will begin removing the heaviest coal tar sealer from your equipment and tools.

Tarpedo can drastically reduce the effort needed to clean equipment, concrete, and other surfaces by making quick work of coal tar sealers.

Tarpedo dissolves coal tar-based contaminants in seconds and allows surfaces to be rinsed clean with water. Very little mechanical cleaning or scrubbing is necessary, and water usage is greatly reduced due to Tarpedo's highly concentrated and fast-acting formula.

Tarpedo is safe for workers, non-caustic, non-corrosive, compatible with all metals, and is safer on painted surfaces than other cleaners.

Tarpedo can also be used to remove heavy oils, grease, asphalt, and other oil-based contaminants.



- **Non-Caustic / Non-Corrosive**
- **High Flash Point Formula**
- **Safe on All Metals**
- **Safe on Painted Surfaces**
- **Highly Concentrated**
- **Rinses Easily with Water**

REMOVES	APPLICATIONS	AVAILABLE PRODUCTS
Coal-Tar, Asphalt, Heavy Oil, Grease, Oil, Bitumen	Surface cleaning of: Sealing Equipment, Tools, Concrete Surfaces	BF2601 - Tarpedo - 1 Gal Can (4/cs)
		BF2605 - Tarpedo - 5 Gal Pail
		BF2655 - Tarpedo - 55 Gal Drum

TIPS AND BEST PRACTICES

- Tarpedo should be used at full strength when removing coal tar sealer. Do not dilute.
- Tarpedo can degrade plastics, rubber, and other sensitive parts over time. If applied to these surfaces, simply rinse with water to deactivate.
- Do not apply Tarpedo to equipment or surfaces that exceed 250°F (121°C).
- Tarpedo is compatible with all metals.
- Tarpedo is safe on painted surfaces with an intact clear coat. After application, simply rinse or wipe clean before the Tarpedo dries to avoid any possible dulling or hazing of the surface.
- Nitrile gloves and eye protection are recommended when using Tarpedo.
- Pump sprayers with Viton®, Teflon®, or other solvent resistant components are highly recommended to extend the life of the sprayer.
- **Please read the Safety Data Sheet and all directions before using Tarpedo.**

DIRECTIONS

Use full strength to remove ready mix and concentrated coal tar sealers, asphalt, adhesives, grease, oil and other tough contaminants.

1. Apply Tarpedo® directly to surface to be cleaned.
2. Use cloth or rag to wipe surface clean.
3. Rinse thoroughly with water.
4. Repeat as needed for heavy deposits.

CAUTION: Product may damage surfaces like automobile headlights and taillights. If product is sprayed on these surfaces, rinse immediately with water.

*Protect plastic (Lexan™), rubber, waxed and other similar vehicle surfaces from overspray.

Tarpedo is compatible with all metals. Avoid use on natural rubber, neoprene, or other incompatible materials. Pump sprayers with Viton®, Teflon®, or other solvent resistant components are highly recommended to extend the life of the sprayer. Contact BioChem Industrial Cleaners for more information on material compatibility.

Item #	BF2601, BF2605, BF2655
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal
Container Types and Weights:	Steel Can - 1 gal - 9.25 lbs
	Steel Pail - 5 gal - 44.5 lbs
	Steel Drum - 55 gal - 432.5 lbs

Scent:	Mothballs
Color:	Colorless / Slightly Yellow
Flash Point:	145°F (62.7°C)
Base Type:	Petroleum
Solvency/KB:	Not Measured
VOC Content:	100%
Relative Density:	0.9 g/m ³
Restricted from Sale:	None
California Prop 65 Warning:	Naphthalene

DANGER: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

PREVENTION: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use explosion-proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release into the environment. Wear eye protection, face protection, protective clothing, protective gloves. Ground / bond container and receiving equipment.

RESPONSE: IF SWALLOWED: Immediately call a doctor or a poison center. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. Do NOT Induce vomiting. If exposed or concerned: get medical advice / attention. In case of fire: Use media other than water to extinguish. Collect spillage.

STORAGE: Keep container tightly closed. Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

EMERGENCY TELEPHONE NUMBER PERS:
(800) 633-8253



WARNING: This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY



08122026